

Product Specifications		Version	A	
		Page	1	
Model	C31.545M	Date	01/06/2022	
Name	TopX Mini Selfpower USB DOCK			
Picture		Features:		
		<ol style="list-style-type: none"> <li>1,USB 3.0 host self power</li> <li>2,Line end cable USBC plug connector laptop. support plug and play</li> <li>3,Upstream Transmission rate up to 5Gbps.</li> <li>4,Downstream USB3.0A*2. 5Gbps data rate transfer. Compatible with USB2.0/1.1 device.</li> <li>5,The wire network supports 10/100/1000Mbps adaptive</li> <li>6, Card slot support SD and micro SD reading and writing editing.</li> <li>7,External PD power supply charging for laptop through PD in port.</li> <li>8,audio jack support 3-pole jack audio,microphone input and headphone output</li> <li>9,Video output can setting to extenden.mirror.main display, rotating.</li> <li>10,The side port HDMI and DP output 4096*2160@60</li> <li>11,rear end HDMI output 4096*2160@60 ( alt mode host DP1.4)</li> <li>12,support triple displays at same time ( alt mode host)</li> </ol>		
Description		Package content	Operating system:	
<p>Triple displays 4k@60 mini Dock. support video audio conver. USB expand.adding card reader function and PD chargered. Build 10/100/1000Mbps adaptive wired network. External PD power USBC port for laptop charging. It can connect to laptop through line end USC plug. for you providing a fully -compatible docking solution.</p>		Mini USB3.0 Docking Station *1 User Manual *1	Windows Mac Os Android Chrome Os Ubuntu	
Specification				
Hardware		Functions		Exterior
Up stream ports	End line cable type C plug	Video extension		DOCK
Down stream port	USBA and USBC RJ45 3.5" audio jack HDMI DP SD TF	Data conversion		End line cable black
Power button	Green	USB Port expand		
Chipset	DL6950 VL813	wired network connect		
Flash	8MB	SD/TF card read and wirte		
SDRAM	DDR3*2	audio expand		
Power Supply	self power			
Power Plug	PD power(other)			
Power Consumption				
Rated Voltage/ requency /current				
Dimensions		Certification (认证)		
Unit Dimensions	130*60*15 MM (L x W x H)	CE-EMC		NO suitable
Weight	100G	CE-RTTE		
Housing Material	ABS aluminium alloy	CE-LVD		
All Weight	210g	FCC DOC		
Package Dimensions	190*105*21	FCC ID		
		ROHS		
Operating Temperature	0°C~40°C	Reach		
Storage Temperature	-10~70°C	3C		
Relative Humidity(Operational)	10%~90%,noncondensing	Others		
Relative Humidity(Storage)	10%~90%,noncondensing	Method		
Drop test (1 Meters)	5 st	Performance		
Cycle work (hours)	24H	Reliability		